

Decision making at a glance

iLog analyses the data for you and its multifunctional display presents you all relevant information on the spot without PC download. Your decision to accept or reject goods can be made right away, saving you time and effort.

Convenient Quick Download

With its new electronic technology iLog communicates quickly, providing you with the convenience of high download and programming speeds. So when it comes to documentation and traceability obligations iLog helps you to get more done.

0.1°C Resolution Providing an Information Advantage


Due to its combination of great resolution and high accuracy, the iLog can detect and record the smallest fluctuations in temperature for the tight monitoring of critical conditions. You benefit from the confidence and security of having precise relevant information at your fingertips.

iLog family of intelligent loggers

iLog intelligent loggers provide you with the technological facilities to introduce total quality control for temperature and humidity sensitive products and services while supporting your compliance with the stringent monitoring requirements of today's markets. With the extended functionality of its display the iLog supplies you instantly with all the information required.

Special Features

- **Bookmark via Magnet Swipe:** Mark readings you wish to identify by swiping a magnet over the iLog label. As this action can be performed only using a start magnet JA-KEY, this convenient feature may be used to register when the iLog has been inspected by an authorised party.



Current reading of humidity sensor



Highest reading of humidity sensor after logging has ended, upper alarm specification was exceeded, battery is low.



Logger armed for timer start, (internal temperature and humidity sensor activated)



Average reading of internal sensor (in degrees celsius)



Lowest reading of left external sensor (in degrees fahrenheit).



Time the right external sensor spent under lower alarm specification at end of logging cycle

- **LCD Functionality:** You can see comprehensive information on status of logging cycles, statistics, and alarm conditions on iLog's multifunctional display. Console Software allows you to define the time iLog pauses on each display before scrolling to the next.
- **Available Sensor Combinations:** Choose the sensor combination required for your application:
 - Internal Sensor
 - Internal and External Sensor
 - Two External Sensor
 - Internal Temperature and Humidity Sensor
- High Temperature Option for External Sensor -20 to +100C (-4 to 212°F)
- Internal Sensor iLog immersion rated IP67
- User replaceable battery



ESCORT iLog Temperature Loggers

ESCORT iLog HumidityLogger